




AP25 BOS



description

- Self contained, semi-portable odor and bacteria abatement system
- Automatic unattended operation
- Rugged stainless steel construction
- Plugs into standard 120VAC outlet
- Integral hour meter included
- Complete with hose and hose attachments

applications

- Heavy commercial or industrial odor situations
- Dumpsters
- Compactors
- Waste storage areas
- Lift stations

the technology

A self-contained, semi-portable unit, the AP25 BOS is designed to control odors and specific contaminants in dumpsters, compactors, waste storage areas, laundries, and other commercial applications. The AP25 BOS utilizes

activTek's tested ActivePure® technology to effectively treat interior air and exposed surfaces, reducing odors and odor-causing bacteria at the source.

Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure® technology substantially reduces microbial populations on surfaces. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease.



specifications

BOS DUMPSTER	US40303 (120v) - US50290 (220v)	
electrical	120VAC, 3 amp., 60 Hz	220VAC, 1.5 amps, 50 Hz
mechanical	65 CFM	2.375" flex hose with connections
controls	hi/off/lo - 3 position toggle switch	hour meter
dimensions	25"L x 10"W x 18"H	64cm L x 25cm W x 46cm H
weight	20 pounds	9 kilograms

The AP25 BOS is ideally suited for heavy odor abatement for dumpsters, trash compactors, and sewer lift stations.

applications list

- Dumpsters
- Laundries
- Recycle centers
- Compactors
- Hotels
- Supermarkets
- Sewer lift stations
- Food processing plants
- Waste storage areas
- Nursing homes

installation details

Locating the AP25 BOS

The AP25 BOS should be protected from extreme temperatures for longer product life.

The AP25 BOS will operate best in dry, cool environments. Avoid placing unit in an area that may

flood. When only a damp or flooded area is available, use a stand or other suitable mounting device to avoid damage to the unit and keep it above the wet area.

START-UP PROCEDURE

1. Determine a suitable location to mount unit and plug into a standard three prong electrical outlet (if unit is to be hard wired, all connections are to be made by a certified licensed electrician).
2. If connecting to a compactor or dumpster:
Connect the provided 2-3/8" flexible hose to the BOS unit. Connect the other end of the hose to the dumpster/compactor (Trim hose as needed.

Extensions are available if the hose is too short for your application). If a suitable location for the hose to enter the compactor/dumpster is not available, drilling a hole into the compactor/dumpster may be required.

3. Turn equipment on. Equipment is designed to run 24 hours per day.

Distributed By: